

DIRECTIONS FOR USE

DAZZLE FLOOR FINISH utilizes a unique combination of synthetic polymers to produce a floor finish that can withstand the rigors of frequent burnishing. Designed for easy maintenance of its incredible "wet look" gloss, DAZZLE FLOOR FINISH displays superior scratch and scuff resistance significantly reducing the frequency of restoration and recoating operations. For best results, apply a minimum of two coats of DAZZLE FLOOR FINISH to a floor previously sealed with FIRST REFLECTION or DIAMOND SEAL FLOOR SEALERS.

Always apply DAZZLE FLOOR FINISH to a floor sealed with FIRST REFLECTIONS or DIAMOND SEAL FLOOR SEALERS. With a clean, rayon/cotton blend mop, apply DAZZLE by first "framing" the area to be finished. Use mop to apply a line of seal around the area to be sealed, then go back and fill in the "framed" area with a gentle side to side mopping motion, being certain to overlap each pass slightly. If a rectangular finish applicator is used. Be certain, that the applicator head has been thoroughly rinsed. Apply seal in thin, unbroken line, be certain that each pass slightly overlaps the previous one. Let each coat dry to the touch before recoating. Dry time is approximately 30 minutes. High humidity could prolong dry time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer.

Apply each subsequent coat of DAZZLE FLOOR FINISH using the same method outlined above. For maintenance of "wet look" gloss, burnish frequently with an UHS Electric, Battery or Propane burnisher.

MAINTENANCE OF DAZZLE FLOOR FINISH: Dust mop daily - using dust mops treated with FIRST ATTRACTIONS DUST MOP TREATMENT. Dirt and dust can abrade and scratch your finishes destroying their natural luster. Damp mop regularly with EXCEL FLOOR CLEANER. The highest gloss come only from clean floors. Dirt acts as a barrier to light reflection, causing your floors to look dull and lifeless. To restore lost luster, burnish regularly.

Mop on LUSTRE RESTORER before using Ultra High Speed (UHS) burnisher will bring back that spectacular "wet look" shine. To restore lost shine, spray buff at least twice per week. CRYSTAL IMAGE SPRAY BUFF LIQUID repairs marks, deep scuffs and scratches quickly. When used in a regular spray buffing program, it helps floor finishes to "snap back" to their original luster to extend finish life and eliminate time consuming recoating.

DAZZLE

FLOOR FINISH

HIGH SOLIDS BURNISHING
FLOOR FINISH

REACTIVE POLYMER
MATRIX MAXIMIZES
BURNISHING RESPONSIVENESS

COMBINES SUPERIOR
"WET LOOK" GLOSS WITH
INCREDIBLE DURABILITY

CAUTION

May irritate eyes. Do not take internally.
See side panel for additional precautionary
statements and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

PROFESSIONAL SECRETS TO EFFECTIVE FLOOR CARE

- To ensure DAZZLE reaches its maximum gloss potential, always apply to floors with at least two coats of a floor seal, like FIRST REFLECTIONS. Maximum gloss can only be achieved on smooth, level floors. Floor sealers smooth out your floors surface imperfections to allow for maximum light reflectance.

- Do not use your stripping or rinsing mop or bucket for the application of floor finishes. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of finish.

- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.

- Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish.

CAUTION

Concentrate may irritate eyes. Do not take internally. Avoid contact with eyes and mucous membranes. If in eyes, flush with large quantities of cool water for at least 15 minutes. If irritation persists, obtain medical assistance. If swallowed, contact physician or poison control center immediately. Give person several glasses of cool water and induce vomiting.

KEEP OUT OF REACH OF CHILDREN

| Hazardous Materials Information System (HMIS) | | | National Fire Protection Association (NFPA) | | | |
|---|---|----------|---|---------------|---------------------|---|
| HEALTH | 1 | Severe | 4 | Extreme | HEALTH | 1 |
| FLAMMABILITY | 0 | Severe | 3 | High | FLAMMABILITY | 0 |
| REACTIVITY | 0 | Moderate | 2 | Moderate | REACTIVITY | 0 |
| PERSONAL PROTECTION | 8 | Slight | 1 | Slight | SPECIAL PRECAUTIONS | 0 |
| | | Minimal | 0 | Insignificant | | |

170293005

NET CONTENTS:

5 6 20 30 55
GALLONS