

SECTION 1: Product and company identification

Product name : Chisel – Floor Stripper
Use of the substance/mixture : Floor wax stripper
Product code : 1716
Company : Total Solutions
P.O. Box 240014
Milwaukee, WI 53224 - USA
T (414) 354-6417
Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Corr. 1C H314
Carc. 2 H351
STOT RE 2 H373
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : Causes severe skin burns and eye damage
Suspected of causing cancer
May cause damage to organs through prolonged or repeated exposure
Precautionary statements (GHS-US) : Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Do not breathe mist, spray
Wash thoroughly after handling
Wear eye protection, protective clothing, protective gloves
If swallowed: rinse mouth. Do NOT induce vomiting
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If exposed or concerned: Get medical advice/attention
Immediately call a doctor, a POISON CENTER
Get medical advice/attention if you feel unwell
Specific treatment (see First aid measures on this label)
Wash contaminated clothing before reuse
Store locked up
Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable
Full text of H-phrases: see section 16

3.2. Mixture

Chisel – Floor Stripper

Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
Glycol Ether EB	(CAS No) 111-76-2	7-13	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
potassium hydroxide	(CAS No) 1310-58-3	1-5	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314
2-aminoethanol, ethanolamine	(CAS No) 141-43-5	1-5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335
disodium metasilicate	(CAS No) 6834-92-0	0.1-1.5	Skin Corr. 1B, H314 STOT SE 3, H335
Cocoamide	(CAS No) 8051-30-7	0.5-1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318
2,2'-iminodiethanol, diethanolamine	(CAS No) 111-42-2	0.1-1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT RE 2, H373

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage. May cause cancer. May cause damage to organs through prolonged or repeated exposure.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	: Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water moderately and if possible collect or contain it. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective goggles. Protective clothing.
Emergency procedures	: Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Chisel – Floor Stripper

Safety Data Sheet

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers.
Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Add ALWAYS product to water for dilution/mixture. Never add water to this product.

Storage conditions : Keep container closed when not in use. Store in original container.

Incompatible products : strong acids.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: (strong) acids.

Storage area : Keep only in the original container. Store in a dry area. Store in a cool area.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
2-aminoethanol, ethanolamine (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (ppm)	6 ppm
ACGIH	Remark (ACGIH)	Eye & skin irr
2,2'-iminodiethanol, diethanolamine (111-42-2)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	Liver & kidney dam
potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³

8.2. Exposure controls

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : clear, pink. Liquid.
Odor : detergent odor
Odor threshold : No data available
pH : 12.75 - 13.75
Melting point : No data available

Chisel – Floor Stripper

Safety Data Sheet

Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.05 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: < 15 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO₂ are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May be corrosive to metals. strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
2-aminoethanol, ethanolamine (141-43-5)	
LD50 oral rat	1720 mg/kg female
LD50 dermal rabbit	1000 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
2,2'-iminodiethanol, diethanolamine (111-42-2)	
LD50 dermal rabbit	8180 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight

Chisel – Floor Stripper

Safety Data Sheet

potassium hydroxide (1310-58-3)	
LD50 oral rat	273 mg/kg (Rat)
ATE CLP (oral)	273.000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 12.75 - 13.75
Serious eye damage/irritation	: Not classified pH: 12.75 - 13.75
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Glycol Ether EB (111-76-2)	
IARC group	3 - Not Classifiable

2,2'-iminodiethanol, diethanolamine (111-42-2)	
IARC group	2B - Possibly Carcinogenic to Humans

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.

Glycol Ether EB (111-76-2)	
LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver
NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day

Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	: Gastrointestinal complaints.

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

potassium hydroxide (1310-58-3)	
LC50 fish 1	28.6 mg/l (24 h; Pisces; Pure substance)
LC50 other aquatic organisms 1	100 - 1000 mg/l (96 h)
LC50 fish 2	80 mg/l (96 h; Gambusia affinis; Pure substance)
Threshold limit other aquatic organisms 1	100 - 1000,96 h

12.2. Persistence and degradability

potassium hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

potassium hydroxide (1310-58-3)	
Bioaccumulative potential	Not bioaccumulative.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : NA1760 Compounds, cleaning liquid, 8 (Potassium Hydroxide), III
 UN-No.(DOT) : NA1760
 Proper Shipping Name (DOT) : Compounds, cleaning liquid
 Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
 Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
 DOT Packaging Bulk (49 CFR 173.xxx) : 241
 DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
 DOT Special Provisions (49 CFR 172.102) : IB3,N37,T7,TP1,TP28
 DOT Packaging Exceptions (49 CFR 173.xxx) : 154
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
 DOT Vessel Stowage Location : A
 DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Glycol Ether EB	CAS No 111-76-2	7 – 13
-----------------	-----------------	--------

2,2'-iminodiethanol, diethanolamine (111-42-2)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
potassium hydroxide (1310-58-3)	

Chisel – Floor Stripper

Safety Data Sheet

potassium hydroxide (1310-58-3)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.