

DIRECTIONS FOR USE:

DIAMOND SEAL FLOOR SEALER has been specially formulated to solve the problem associated with the maintenance of terrazzo and other porous stone flooring. This unique sealer establishes a reversible bond with stone surfaces to ensure superior adherence. Urethane modifiers give the acrylic matrix incredible strength and durability. Making DIAMOND SEAL an excellent base for the application of high gloss acrylic floor finishes, like DAZZLE, JEWEL and CRYSTAL. Two coats of DIAMOND SEAL levels flooring surface imperfections to maximize the gloss potential of your floor finish.

Always apply DIAMOND SEAL to a newly stripped floor. With a clean, rayon/cotton blend mop, apply DIAMOND SEAL by first "framing" the area to be finished. Use mop to apply a line of seal around the area to be sealed, then go back and fill in the "framed" area with a gentle side to side mopping motion, being certain to overlap each pass slightly.

If a rectangular finish applicator is used, be certain that the applicator head has been thoroughly rinsed. Apply seal in thin, unbroken line, be certain that each pass slightly overlaps the previous one. Let each coat dry to the touch before recoating. Dry time is approximately 30 minutes. High humidity could prolong dry time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer. Apply a second coat of DIAMOND SEAL using the same method outlined above.

After 30 minutes begin applying high gloss floor finishes (i.e. DAZZLE, JEWEL and CRYSTAL). For floor subject to burnishing operation, apply a minimum of four coats of finish. Floors subject to spray buffing operations, apply a minimum of two coats of floor finish.

DIAMOND SEAL FLOOR SEALER

WATER-BASED URETHANE FORTIFIED FLOOR SEALER

SPECIFICALLY FORMULATED FOR MAXIMUM ADHERENCE TO TERRAZZO AND POROUS STONE FLOORING

SUPERIOR BASE COAT FOR ACRYLIC FINISHES SUBJECTED TO EITHER BURNISHING OR SPRAY BUFFING OPERATIONS

CAUTION

May irritate eyes. Do not take internally. See side panel for additional precautionary statements and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

PROFESSIONAL SECRETS TO EFFECTIVE FLOOR CARE:

- Do not use your stripping or rinsing mop or bucket for the application of floor sealers. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of sealer.
- To avoid the accumulations of finish build-up in corners or on baseboards, always the first coat of DIAMOND SEAL no closer than 12 inches from baseboards. Apply second and every other coat up to baseboards.
- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.
- Discard unused finish. Pouring unused finish from your bucket back into the original container can spoil the good finish.

CAUTION

May irritate eyes. Do not take internally. Avoid contact with eyes. Prolonged or repeated contact with skin may cause irritation. Use with adequate ventilation. If in eyes, flush with cool water for at least 15 minutes, if irritation persists, obtain medical assistance. If swallowed, contact physician or poison control center immediately. Give person several glasses of water and induce vomiting. If on skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

1720110295

NET CONTENTS:

Hazardous Materials Information System (HMIS)				National Fire Protection Association (NFPA)		
HEALTH	1	Severe	4	Extreme	HEALTH	1
FLAMMABILITY	0	Severe	3	High	FLAMMABILITY	0
REACTIVITY	0	Moderate	2	Moderate	REACTIVITY	0
PERSONAL PROTECTION	3	Slight	1	Slight	SPECIAL PRECAUTIONS	0
		Minimal	0	Insignificant		