



DESCRIPTION

ASPHALT PATCH is the fast, easy and economical way to make instant, traffic ready road repairs. It keeps roads in a safe condition all year long. ASPHALT PATCH may be used in any weather, and in temperatures as low as 15°F. No involved surface preparation or primer is necessary.

Excellent for repairing asphalt, black top and stone. ASPHALT PATCH can be stored indefinitely. It will not harden until it is tamped, even if the container is not tightly closed.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash hands thoroughly after handling. Wear protective gloves, clothes, and goggles. Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of water for at least 15 minutes. **If skin irritation occurs:** Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Get medical advice/attention if you feel unwell.

Store locked up.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

DISPOSAL

Dispose of contents/container to meet all regulations.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

ASPHALT PATCH

Paving Patch and Pot Hole Filler

DIRECTIONS

Brush dust and dirt away and fill the crack or hole with ASPHALT PATCH and tamp down.

NFPA® RATINGS

Health: 1; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER:

Limestone/1317-65-3;
Petroleum Asphalt Base/8052-42-4;
Petroleum Solvent/68476-34-6;
Quartz/14808-60-7

DANGER

Causes skin irritation.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 5 Gallons

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224
1-800-743-6417



Please Recycle.

1801.060515