

DESCRIPTION

Provides long-term protection even when exposed to steam, damp atmospheres and salt spray. Protects metal parts under sustained temperatures up to 2100°F (1050°C). Dry lubricant acts as a sealant, reduces friction, makes tighter, firmer joints that open easier reducing torque requirements.

USEFUL ON THESE SURFACES:

**Cast Iron • Steel alloys • Aluminum
Copper • Brass • Titanium
Rubber - Natural and Synthetic**

CAUTION-COMBUSTIBLE

May be harmful or fatal if swallowed. May irritate eyes and skin. Prolonged or repeated exposure may cause irritation. Use with adequate ventilation.

FIRST AID:

If Swallowed: Do not induce vomiting. Call a physician immediately.

If Inhaled: Remove person to fresh air. If irritation persists, obtain medical attention.

If In Eyes: Flush eyes and under eyelids with cool water for at least 15 minutes. If discomfort persists see a physician.

If On Skin: Wash with soap and water. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not store in unmarked containers. Store container in cool, dry place. Do not cut or weld on or near this container even when empty. Store away from heat or open flame.

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

GRAPHITE LUBE

Extreme Temperature &
Extreme Pressure Lubricant

- NON-MELTING
- NON-HARDENING

KEEP OUT OF REACH OF CHILDREN CAUTION-COMBUSTIBLE

May be harmful or fatal if swallowed.
See back panel for further precautions and first aid instructions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 55 Gallons

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Clean surface of oil, grease and dirt. Use with grease or gun pressure pump. Keep container tightly closed when not in use.

Note: May harm painted or waxed surfaces. Always test inconspicuous areas before using.

This Product Contains/CAS Number: Aliphatic Petroleum Distillates/8052-41-3; Petroleum Oil/64742-52-5; Graphite/7782-42-5.

NFPA® RATINGS
FLAMMABILITY

HEALTH  REACTIVITY

0336.112403