# **Graphite Lubricant**

### **Product # 336**

High-temperature dry lubricant

This high-grade, dry graphite liquid is designed to eliminate friction and protect high-use equipment from rust and corrosion. It's a durable, heavy-duty lubricant that can endure extreme temperatures up to 900°F. It penetrates deep, dries quickly and sheds moisture to prolong the working life of equipment and machinery.

#### Use on:

- Cast IronSteel AlloysAluminumCopperBrassTitanium
- NOTE: May harm painted or waxed surfaces.

#### **Features and Benefits**

- Offers long-term protection, even when exposed to steam, damp atmospheres and salt spray.
- Protects metal parts under sustained temperatures up to 2100 Degrees F.
- Acts as a sealant, reduces friction and makes tighter, firmer joints.

Properties		<b>Directions</b> Complete directions on product label
Appearance	Black liquid	Clean surface of oil, grease and soils. Use with grease gun or
Fragrance	Solvent	pressure pump.
Ready to use	Yes	
Specific gravity	0.845	NOTE: May harm painted or waxed surfaces. Always test in an
Flash point	130 ° F	inconspicuous area before using.
Stability	1 year	

Active Ingredients	CAS Number
Paraffinic Naphthenic Solvent	64742-47-8
Mineral Spirits	8052-41-3
Petroleum Oil	64742-52-5
1,2,4-Trimethylbenzene	95-63-6
Graphite	7782-42-5

#### Safety

Caution: Combustible May be harmful or fatal if swallowed. Keep out of the reach of children

## DOT Shipping (ground transportation)

Proper Shipping Name: None Class: None ID Number: None Package Group: None



#### Quantities

30, 35 & 55 gallon 5 or 6 gallon 6 X 1 gallon 4 X 1 gallon



Milwaukee, WI 53224 • 1-800-743-6417 • Fax 414-354-9219 • www.athea.com