

This cationic polymer flocculent is designed for fast and efficient clarification of wastewater in industrial waste systems and municipal waste treatment facilities. It uses high molecular weight polymer for rapid settling of solids and suspended debris. This formula is easy to handle and dispense and will help to increase the waste-handling capacity of the system and reduce operating costs.

This biodegradable settling agent is non-toxic and will not harm fish or wildlife when used as directed. Typical applications include primary and secondary clarifier, digesters, settling ponds or basins and reservoirs.

DIRECTIONS

Feed this settling agent directly into the waste stream prior to the clarifier or settling basin. Drip or pump into the system at a point of strong agitation. Use rates may vary from 50 ppm up to 300 ppm (2 quarts up to 3 gallons per 10,000 gallons of waste). For maximum economy and effectiveness, continuous drip application is recommended.

For ponds or lagoons, drip or spray 10 to 20 gallons of settling agent per million gallons of water. Drip directly into waste stream or spray over surface to obtain even distribution of the polymer.

SETTLING AGENT CONCENTRATE

CATIONIC POLYMER FLOCCULENT
QUICKLY AND EFFECTIVELY
PRECIPITATES SILT, CLAY, SLUDGE
AND ORGANIC SOLIDS

CAUTION

May irritate eyes. See side panel for additional precautionary statements and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION

May irritate eyes.

FIRST AID

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse.

See M.S.D.S. for complete safety information.


KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Store at temperatures below 100° F and above freezing. Rinse thoroughly with water before recycling container.

This product contains	CAS Number
Water	7732-18-5
Cationic polymer resin	No CAS Number

0384.013007

NFPA® RATINGS
Flammability



NET CONTENTS:

5 6 20 30 55
GALLONS