

This special wetting agent is designed to help fight stubborn, smoldering fires in upholstery, bedding, paper, hay and brush. Treated water penetrates more quickly, extinguishing the blaze with only 1/3 as much water.

This formula is biodegradable and non-corrosive. It will not harm water tanks or fittings and is compatible with all fire fighting foams and tank protectors.

DIRECTIONS

For increasing the wetting ability of water used in fire fighting, use 1/2 to 1 gallon per 100 gallons of water.

This wetting agent also helps to control dust on unpaved roads and yards. Mix 1 to 2 quarts per 100 gallons of water for spraying over road surfaces.

To hold down the dust from mechanical sweepers, add 1 to 2 quarts per 100 gallons of wash water.

WATER WETTER

CHEMICAL ADDITIVE
INCREASES THE WETTING
AND PENETRATING
ABILITY OF WATER

CAUTION

May irritate eyes.

See side panel for additional precautions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION
May irritate eyes.

FIRST AID

If In Eyes: Flush eyes and under eyelids with water for at least 15 minutes. If discomfort persists see a physician.

If Swallowed: Give several glasses of water and induce vomiting. Call a physician immediately.

If On Skin: Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation is persistent, contact a physician.


If Inhaled: Remove person to fresh air. Call a physician in irritation persists.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked containers. Store container in a cool, dry place.

This Product Contains	CAS Number
Water	7732-18-5
Alkyl Phenol Ethoxylate	9016-45-9



0395.021204

NET CONTENTS:

5 6 20 30 55

GALLONS