

DESCRIPTION

Formulated to provide fast and effective cleaning with steam cleaners, this concentrate quickly removes grime, oil, grease, road film, carbon, black streaks, and other tough soils from fiberglass, vinyl, industrial equipment, concrete, gutters, and vehicle engines.

CAUTION

May be harmful if swallowed. May cause eye and skin irritation. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: Contact a physician or poison control center immediately. DO NOT induce vomiting.

IF IN EYES: Contact a physician or poison control center immediately. Flush eyes with water for at least 15 minutes.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. If irritation is persistent, contact a physician.

See *M.S.D.S.* for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not store in unmarked containers. Do not mix with any other chemicals. Store container in a cool, dry place.

TOTAL SOLUTIONS™

INDUSTRIAL CLEANERS
and DEGREASERS

STEAM AND PRESSURE WASH CONCENTRATE

Strips Away
Dirt and Grime

- REMOVES GREASE AND OIL
- IDEAL FOR FIBERGLASS,
VINYL, CONCRETE
AND OTHER SURFACES

KEEP OUT OF REACH OF CHILDREN

CAUTION

May be harmful if swallowed.
May cause eye and skin irritation.
See side panel for additional precautions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 55 Gallons

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Adjust the feed rate of steam cleaner to obtain the dilution of 1:20-1:40. Heavy deposits may require more concentrate, and lighter deposits may require less.

Be sure to rinse the steam cleaning equipment with clean water after each use. Do not use on aluminum. Spot test first if using on painted surfaces.

This Product Contains/CAS Number: Water/7732-18-5; Sodium Metasilicate/6834-92-0; Sodium Tripolyphosphate/7758-29-4; Sodium Laureth Sulfate/9004-82-4; Potassium Hydroxide/1310-58-3.

NFPA® RATINGS FLAMMABILITY

HEALTH  REACTIVITY

0405•010511