

This non-phosphate dispersant and scale inhibitor was developed as a supplement to chelant, carbonate or phosphate treatments. It is designed to remove and control scale and other deposits caused by calcium, magnesium, barium, aluminum and iron. It also acts as polymeric sludge conditioner and fluidizer and is not degraded by heat like many other dispersants.

APPLICATION

Dosages will vary according to boiler sludge levels. Normal application rates should be between 20 to 100 ppm (3 to 13 ounces per 1000 gallons of boiler water capacity).

May be fed on a "one-shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for industrial process and other large boilers. Product may be mixed with other boiler treatment chemicals and diluted with water for convenient feeding.

SLUDGE TREAT

SUPPLEMENT TO
CARBONATE, PHOSPHATE
OR CHELANT TREATMENTS

CAUTION

Harmful if swallowed. See back panel for further precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION

Harmful if swallowed. Do not take internally. Avoid contact with skin, eyes and mucous membranes.

FIRST AID

If Swallowed: Give person several glasses of water. DO NOT induce vomiting. Obtain immediate medical assistance.

If In Eyes: Flush with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical assistance.

If On Skin: Wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

64592747

NET CONTENTS:

5 6 20 30 55
GALLONS