

DESCRIPTION

Saves production, maintenance, and repair time. Protects and preserves equipment.

Spray on, let set and the fast-acting, penetrating formula goes to work. It loosens the rust or corrosion, making it easy to separate the surfaces.

For use on refrigerator equipment, automobiles, work-shops. Free nuts and bolts. Lubricates locks, hinges, moving parts. Stops and retards corrosion. Stops corrosion on battery terminals.

DANGER: Harmful or fatal if swallowed. Flammable. May cause severe eye irritation. Can cause burning sensation, tearing, and redness. May cause mild skin irritation. Inhalation may be irritating to eyes, nose and respiratory tract. Can cause dizziness, headaches and incoordination. Exposure by ingestion is unlikely since an aerosol, but if occurs: Irritating to the mouth, throat and stomach. Possible aspiration hazard - may cause inflammation of the lungs. May affect the following organs upon prolonged or repeated overexposure: Liver. Kidneys. Nervous system. Lungs and/or respiratory system.

FIRST AID:

EYES AND SKIN: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration.

INGESTION: In the unlikely event of swallowing: Call physician immediately. Do NOT induce vomiting unless directed by medical personnel. Never give anything by mouth to an unconscious person.

WARNING: Product is to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45. Keep away from heat, sparks, flames, and electric arcs. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F(49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN

See Material Safety Data Sheet for complete safety information.

CONTAINS NO OZONE
DEPLETING CHEMICALS!

TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

MULTI-PURPOSE PENETRANT

Non-Conducting Up
To 24,800 Volts

- LUBRICATES
- CLEANS
- LOOSENS NUTS AND BOLTS
- RETARDS CORROSION
- NEVER DRIES
- DISPLACES MOISTURE
- PENETRATES FASTER AND FARTHER

KEEP OUT OF REACH OF CHILDREN

DANGER:

HARMFUL OR FATAL IF SWALLOWED.
FLAMMABLE. MAY CAUSE EYE, SKIN AND
RESPIRATORY TRACT IRRITATION.
CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WEIGHT: 15 oz. (425 g)

Distributed By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Remove cap and point valve opening toward surface to be sprayed. Hold can 4-8 inches away, push button and spray. For stubborn cases, repeat the spray and allow to set for a few minutes.

This Product Contains/CAS Number:

Mineral Spirits/8052-41-3 or 64742-47-8; Synthetic Isoparaffinic Hydrocarbon/64742-47-8; 2-Butoxyethanol/111-76-2; Hydrotreated Heavy Naphthenic Distillates/64742-52-5; Paraffin Wax/None; and Propane/74-98-6.

HMIS® RATINGS: HEALTH - 2,
FLAMMABILITY - 4, REACTIVITY - 1,
PERSONAL PROTECTION - B.

8101•010412