

This product is a catalyzed oxygen scavenger that quickly removes dissolved oxygen from boiler feedwater. It provides additional protection against pitting and corrosion of internal boiler surfaces when used in conjunction with scale and corrosion inhibitors.

**APPLICATION:**

Dosages will depend upon the quantity of oxygen in the feedwater and the feedwater temperature. A small excess will be needed to maintain a control residual in the boiler. Control the level of by maintaining a sulfite level of between 20 - 40 ppm.

Should be fed on a continuous basis to either the condensate return tank or de-aerating section. When feeding from a solution tank, the feed solution should be protected from the atmosphere by means of a floating cover in the tank. If desired and practical, this product can be mixed in a solution tank with other boiler treatment products and fed into the feedwater system or directly into the boiler.

# OXY TREAT

MINIMIZES OXYGEN PITTING  
WORKS IN SYSTEMS WITH OR  
WITHOUT A DEAERATING HEATER

**CAUTION**

May be harmful if swallowed. Irritant.  
See back panel for further  
precautions and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

Sold By:

**CAUTION**

May be harmful if swallowed. Irritant. Do not take internally. Avoid contact with skin, eyes, and mucous membranes.

**FIRST AID:**

**If Swallowed:** Give person several glasses of water and induce vomiting. Obtain immediate medical assistance.

**If In Eyes:** Flush with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical assistance.

**If On Skin:** Wash thoroughly with soap and water.

**KEEP OUT OF REACH OF CHILDREN**

THIS PRODUCT CONTAINS	CAS NUMBER
Water .....	.7732-18-5
Sodium Hydroxide .....	.1310-73-2
Sodium Metabisulfite .....	.7681-57-4
Sodium Sulfite .....	.7757-83-7

0927-021909

**NET CONTENTS:**

5     6     20     30     55

GALLONS