

FUEL TREAT is an easy-to-handle liquid designed for use in fuel systems where problems exist in both the storage tank and at fireside. FUEL TREAT reduces the viscosity of residual fuel oils and has a fluidizing effect at all temperatures, which provides more uniform and faster pumping. Sludge that typically clogs fuel strainers, nozzles, preheaters and lines is dispersed throughout the fuel. FUEL TREAT makes the organic/inorganic deposits in the fuel system and at the burners more friable.

FUEL TREAT forms a protective film on internal surfaces of storage tanks and piping to reduce corrosion and deposit build-up. FUEL TREAT combines an effective combustion catalyst system, emulsifying agents and solvents that protect boiler tubes and refractory brickwork by deactivating the vanadium oxides and sodium salts.

Fuel oil treated with FUEL TREAT burns cleaner and more completely thereby reducing emission problems associated with particulates, sulfur dioxide and sulfur trioxide. It provides superior protection against cold-end stack corrosion.

APPLICATION

FUEL TREAT is completely soluble in all fuel oils. Initial dosages of FUEL TREAT is 2 gallons per 1000 gallons of fuel (1 quart per 125 gallons). Maintenance dosage of FUEL TREAT is 1 quart per 1000 gallons of fuel oil (4 ounces per 125 gallons).

It is advisable to add FUEL TREAT directly to the fuel oil storage tank just before the tank is refilled so that incoming oil will provide sufficient agitation and mixing.

FUEL TREAT

ALLOWS FUEL TO BURN CLEANER

EXCELLENT
DISPERSING PROPERTIES

CAUTION - COMBUSTIBLE

May be harmful or fatal if swallowed.
Eye irritant.

Keep away from heat, spark and open flame.

See side panel for additional precautions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION - COMBUSTIBLE

May be harmful or fatal if swallowed. Eye irritant. Keep away from heat, spark or open flame. Do not take internally. Avoid contact with eyes.

FIRST AID

IF IN EYES: Flush eyes and under eyelids with water for at least 15 minutes. Obtain medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation is persistent, contact a physician.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting.

IF INHALED: Remove person to fresh air. Obtain medical attention.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked container. Store container in cool, dry place. Keep away from strong oxidizing agents.

This product contains	CAS Number
Light Aromatic Solvent Naptha	64742-95-6
1,2,4-Trimethylbenzene	95-63-6
Fuel Oil Conditioner	Proprietary
Corrosion Inhibitor	Proprietary
Xylenes	1330-20-7
Cumene	98-82-8

0961.021309

NFPA® RATINGS



NET CONTENTS:

5 6 20 30 55
GALLONS